

Docket Number: YO998167

Error Correlation for Wireless Networks

FIELD OF THE INVENTION

5 The present invention is directed to the field of
wireless networking. It is more specifically directed to
error correlation in wireless networks.

BACKGROUND OF THE INVENTION

10 It is generally known that mobile and non-mobile wireless
network performance is generally very dependent upon the
location of the end user. For example, in RF networks
(e. g.,... cellular telephones), moving out of a service
provider's basic coverage area results in high error
rates and/or dropped connections. It is important for a
service provider to map the coverage area and find out
areas where messages cannot penetrate called dead zones.
15 These dead zones can change depending on time of day,
changing interference generators, and even seasonally.

It is advantageous for a service provider to know the dead zones of a service. Because of the difficulty to determine small dead zones the service provider may not actually be knowledgeable of the dead zones of a particular service. This problem is compounded when the dead zones change dynamically due to known and oftentimes unknown influences. Additionally, more often than not these dead zones are sensitive to the communication channel frequency. Presently a service provider is not always able to notify its users in a particular area of channel dead zone mappings and/or a user's approaching or being within a dead zone. Knowing that a dead zone is channel dependent would enable a service provider to indicate the best channels to be used in particular areas automatically or otherwise. It would thus be extremely useful for a service provider to continuously know the dead zones of a service and or service frequency both as it is statically and as it changes dynamically.

SUMMARY OF THE INVENTION

It is thus an aspect of this invention to establish a protocol and method for end users of mobile stations to report regions with high error rates and/or are dead

zones. The protocol is such as to yield the error occurrence, error rate and/or the address of the end user. In some embodiments it also contains location information and time of day information. This
5 information may be collected from all or a portion of users every time there is a significant transmission difficulty and/or an abundance of errors. The collected data forms a database which is analyzed to generate coverage maps. This may include the dynamic aspects of
10 the mobile network.

In another aspect of this invention, each mobile station periodically compares its current location with the data base. The results of this comparison enables the mobile unit to anticipate connection problems. In still another
15 aspect of the invention, the comparison is performed by the service provider which notifies the end user.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, features, and advantages of the present invention will become apparent upon further
20 consideration of the following detailed description of

the invention when read in conjunction with the drawing figures, in which:

FIG. 1 shows an example of the invention in an office environment in which a mobile network is inside near a building also having a traditional wired local area network, wherein the system has three base stations having wireless access to a mobile user on a wireless network;

FIG. 2 shows an embodiment of the present invention for a field environment with a mobile network including a mobile unit controller which has a cellular radio tower which supports a plurality of mobile users on a wireless LAN; and

FIG. 3 shows an example of a system implementing this invention in an office environment connected via a wired LAN, including a system controller connected to a plurality of mobile users error generators 320, and to an error receiver.

DETAILED DESCRIPTION OF THE INVENTION

Docket Number: YO998167

One embodiment of this invention establishes a protocol and method for mobile stations to report regions with high error rates and/or dead zones. It is advantageous that the protocol yield not only the error rate and
5 address of the end user, but also yields location information and/or time of day information. This information is collected in a service provider database. The database is formed from all user notifications every time there are significant transmission errors. The
10 collected data is analyzed to generate coverage maps which also include the dynamic aspects of the mobile network.

In a particular embodiment, mobile stations and/or the service provider periodically compare their current
15 location with the maps. In this case the mobile unit and/or the service provider can anticipate connection problems at the particular user location. In some cases the service provider notifies the end user of a particular channel to use in the particular location for
20 best communication.

An example embodiment relates to an office environment in which a mobile network is inside and/or near a building

Docket Number: YO998167

also having a traditional wired local area network.

Figure 1 shows a system having three base stations 110-112 having wireless access to a mobile user 120 on a wireless LAN 130. These base stations 110-112 are

5 generally fixed and connected into the wired building LAN 130 through which they communicate to each other over the wired LAN.

The base station also having ability to communicate with a plurality of users located within its coverage area

10 range such as user 120.

In an embodiment, the mobile unit checks for errors on all incoming messages. This may be accomplished using CRC or another error detection mechanism. When the error rate for a mobile user rises above a pre-set threshold,

15 the mobile unit transmits an error message. In some cases, the mobile unit uses an enhanced error reporting method to provide a higher probability of correct transmission of the error message. The error reporting method includes such things as transmitting at an above

20 normal power level and/or using one or more alternate frequencies. When any of the base stations receive an error message, it alerts the other base stations of the error condition. In some cases, all the base stations

automatically or manually search for the mobile user
sending out the error message. In one embodiment, the
user reporting the error enters an error reporting mode,
and stays in that mode until it receives an error report
5 acknowledge from a base station or until a timeout occurs
the base stations employ a moveable directional antenna
to traverse an arc and locate the direction of greatest
signal strength from the user reporting the error. When
three (or more) base stations have established the
10 direction, a triangulation algorithm is used to calculate
the exact location of that mobile user. The base station
closest or the one receiving the highest signal strength
level from that user to that user, transmits an
acknowledgment to the mobile unit, and the reporting
15 mobile unit exits the error reporting mode. In some
cases there is a constantly updated data base that
contains records of all error messages. This data base
is processed to extract recurring error trends. This
includes locations that are dead zones for one or more
20 communicating channel frequencies in combination with
particular time of day that are problematic. The
availability of the data base allows mobile stations to
periodically query the data base to determine if the
user is entering into a known problem area or condition.

The mobile station can then inform the end user of the appropriate steps to take to maintain connectivity such as change antenna direction, channel, etc.

Another example embodiment of the present invention
5 relates to a field (outdoor) environment with a mobile network. Figure 2 shows a mobile unit controller 200 which has a cellular radio tower 240 which supports a plurality of mobile users on a wireless LAN 230. A typical wireless user 250 is equipped with the ability to
10 determine its location using the existing global positioning system (GPS) 210 technology. The process in this embodiment is similar to the previous embodiments, except in that the mobile system controller 200 knows the user's 250 position and includes that information in an
15 error message. In this case, since there is wireless connectivity to the GPS satellite 210 there is no need for triangulation in this embodiment. Thus, this embodiment lends itself to mobile devices that already have GPS equipment installed. The devices may be in
20 cars, trucks, buses, boats etc.

There are many ways to implement a system implementing this invention in the office environment connected via a

wired LAN. Such an embodiment is shown in Figure 3.

Figure 3 shows a system controller 310 connected to a plurality of mobile users error generators 320, and to an error receiver 330. The error receiver 330 feeds

- 5 received errors to an error generator's location finder 340. The location finder 340 feeds an error database 350. The error database 350 is connected to a time of day clock 360. The database 350 feeds, the error data, location and time of day to a database processor 370.
- 10 The processor 370 correlates groups of errors and feeds the correlated data to an error map generator 380 which generates maps of dead zones for the mobile service.

- In some embodiments, the error data includes the channel
- 15 frequency and/or the time of day and/or the location of the mobile user 320 that generates the error signal. The system controller 310 relays the error map to all the users 320 near or at a dead zone. In this case, the mobile users 320 continually check for errors on all
- 20 incoming messages. This may be accomplished via CRC or another error detection mechanism. When the error rate of a user 320 rises above the preset threshold, the user transmits an error message. The error message can contain a unique user identifier such as MAC address, TCP/IP

address etc., dependent upon the system and the protocol being employed by the mobile system provider.

In an example embodiment, the mobile user's 320 unit uses one of the available methods of assuring a high
5 probability of correct transmission of the error message to the error receiver 330. This may include using higher transmit power and/or using an alternate channel frequency. When the system controller 310 receives the mobile error message generated by the mobile user's unit
10 320 the other stations and/or mobile users are alerted that there is an error condition. The location finder 340 searches for the location of the mobile user sending out the error message.

In an example embodiment of the location finder, this is
15 done by all the base stations using respectively controlled moveable directional antennae to traverse an arc and locate the direction of greatest signal strength. When three (or more) base stations have established the direction, a triangulation algorithm is used to calculate
20 the exact location of the mobile user. In some case the base station closest to the user transmits an acknowledgment to the mobile unit, and the mobile user's

unit 320 exits "error reporting mode". Alternatively,
the mobile unit can repeat the error message for a fixed
amount of time or repeat the message a fixed number of
times and exit "error reporting mode" independent of base
5 station interaction. This prevents a lock out situation
in areas of very poor reception. In still another
embodiment the GPS is used even in an office environment
to satisfy the location finder's requirement.

There is a constantly updated error data base 350, that
10 contains records of all error messages. This data base
350 may form or be contained within a network management
station within one or more of the base stations.
Alternatively the database 350 may be replicated at all
of the mobile units. This data base 350 can be
15 manipulated to extract any recurring error trends which
indicate regions that are "dead zones" and/or
combinations of locations and times that are problematic
etc. When the data base 350 is established, it is
advantageous for the system controller 310 to
20 periodically query the database processor 370 to
determine if a particular user 320 is entering into a
known problem area or condition. The system controller
may inform the end user of the appropriate steps to take

to maintain connectivity. This is done via an audible alarm and/or a display at the user's 320 device. In some cases the user is told to change direction, channel, power level etc.

- 5 In the outdoor environment with a mobile network shown in Figure 2, there are cellular radio towers supporting the mobile users 320 on a LAN 390. In this case LAN 390 is a wireless LAN. In addition, the mobile user's units 320 are equipped with the ability to determine their location
10 using existing global positioning system (GPS) technology for the location finder 340. The process in this embodiment is similar to the office embodiment, except that the mobile user's unit 320 knows the user's position and includes that information in the error message. There
15 is no need for triangulation in this embodiment. This embodiment lends itself to mobile devices that already have GPS equipment installed in cars, trucks, buses, boats etc. In an alternative embodiment of the outdoor environment also makes use of triangulation methods for
20 the location finder 340.

In an alternate embodiment the mobile users enter a proposed trip route into a system containing both GPS

location equipment and the present system as Figure 3 to
develop and generate dead zone mapping 380, to request
routing and mobile service operational data. The system
controller 310 responds and informs the user of a best
5 route and/or channel/s and for continual mobile service
and/or of areas along the route where communication
coverage is questionable. In some cases the system
controller 310 proposes and displays alternative routes
which maintains different levels of mobile system
10 connectivity automatically or in response to a user's
request.

The concepts of the present invention may be implemented
in many ways and in different packages. These include as
in a method, system and/or a computer device to perform
15 part or all of the steps of the method and/or system
functions. Thus in one embodiment the invention is a
method to detect dead zones in a wireless network. The
network having a plurality of users being interconnected
within the wireless network. The method includes a first
20 user communicating via the wireless network. The first
user measuring and detecting a message error rate while
communicating. The first user broadcasting an error

message to a base station when the error rate exceeds a predetermined error threshold level.

09840517-04301
T0220-279486

The base station obtaining a location of the first user and incorporating the location in a database of dead

5 zones for the wireless network. In general each of a subset of the users has a mobile unit forming a mobile user connection with the wireless network. In an example configuration the wireless network includes a plurality of cellular phones and/or a plurality of portable

10 computing devices interconnected via a wireless local area network. In some cases the method further includes a step of deploying a subset of the users within at least one building. An alternate invention embodiment is providing a method for error reporting in a mobile

15 network having a plurality of members. The method includes the step of at least one of the members keeping track of the number of errored packets in a packet window. When the number of errored packets exceeds a predetermined threshold value, the one member enters an

20 error transmit reporting mode and reports an error condition to a base station. The base station obtains the location of the member or the member provides its location to the base station.

In some cases the step of error detecting includes cyclic error detection, checksum calculation; and/or parity checking or another error detecting scheme. In some cases the error threshold level ratio is set at a
5 predetermined value. The value is usually between 1 in a 1000 and 1 in a billion. A high value is such as to guarantee clear reception of the transmitted data.

Generally, the error message is broadcast with a signal having a high probability of reception by the base
10 station in a dead zone. This may be at a higher power level, a lower transmission rate and/or a different frequency. In some case the step of broadcasting the error message is performed using 2-10 times the power level of normal message transmission and/or the step of
15 broadcasting the error message is via a particular transmission channel with a greater probability of reception in the location, and/or the step of broadcasting the error message is at a data rate that up to ten times slower than the normal data rate. In some
20 cases the time when the error occurred is included in an error message from the member detecting the error and is sent to the base station. Sometimes a unique identity of

the member unit where the error was detected is included in an error message from the member to the base station. In some cases, the step of obtaining location information includes rotating a direction of at least one antenna of
5 a group of antennae to determine the member location information by triangulation, and/or the step of obtaining location information includes employing a wired LAN connecting multiple base stations.

In particular embodiments, the method includes having the
10 base station issue an acknowledge to the first user, and the first user ending an error transmit mode. In some cases, the step of broadcasting the error message is repeated a fixed number of times, and said first user ending an error transmit mode, or the step of
15 broadcasting the error message is repeated over a fixed time interval whereupon the first user ends the error transmit mode and/or the step of logging the error message and location of the dead zone for transmittal to the base station at a later time whereupon the first user
20 ends the error transmit mode and/or data extracted from the error messages are stored in a database for future manipulation and retrieval, and/or the database is resident at a network management station, and/or the

database is replicated and resident at all network base stations, and/or the database is replicated and resident at all mobile network devices; and/or the step of forming a database of error reports, and extracting a set of

5 features from the database, and/or the step of extracting includes determining the actual level of service obtained for said mobile network; and/or the database forms a map of dead zones in the building and/or includes the step of examining the database to determine an occurrence of a

10 repetitive time dependent feature.

In another aspect of the invention a method is provided to detect dead zones in a wireless network employed in an outdoor environment. The network has a group of users interconnected within the wireless network. The method

15 includes a first user communicating via the wireless network. The first user measures and detects a message error rate while communicating. The first user broadcasts an error message to one of its base stations when the error rate exceeds a preset error threshold

20 level. The base station obtains the location of the first user from the first user or determines the location with its own means, and it incorporates the location in a database of dead zones for the wireless network. In some

cases the step of obtaining includes employing a Global Positioning System (GPS) module or a Loran-C Positioning System module resident in the base station and/or the first user station, and/or each of a subset of the users

5 has a mobile unit forming a mobile user connection with the wireless network. Sometimes the wireless network includes a plurality of cellular phones and/or the GPS module is built into the mobile unit interconnected with the wireless network.

10 In some cases, the wireless network includes a plurality of vehicles interconnected via a wireless wide area network and/or the method includes a step of deploying a subset of the users within at least one building.

In a particular embodiment of the method the mobile

15 network has a plurality of members. The method further includes one or more of the following steps: at least one of the members keeps track of the number of errored packets in a packet window; the member device enters an error transmit reporting mode when the number of errored

20 packets exceeds a predetermined or dynamic threshold; the member device reports an error condition to one of the base stations; and the base station obtains the location

of the member. The dynamic threshold may be related to such things as network traffic rate and/or previously obtained dead zone data. The step of error detecting may include cyclic error detection, parity checking, and/or
5 checksum calculation.

In many cases the error message is broadcast with a signal having a high probability of reception by the base station in a dead zone. In some cases the unique identity of the member detecting the error is included in
10 the error message from the member to the base station and/or the step of obtaining location information includes querying the Global Positioning System to determine the members location.

In some embodiments, the method includes the step of the
15 base station issuing an acknowledge to the first user, and the first user ending an error transmit mode upon receiving the acknowledge. In other cases the step of broadcasting the error message is repeated a fixed number of times, and/or the error message is repeated over a
20 fixed time interval.

In a further embodiment, the method includes the step of logging the error message and the location of the dead zone for transmittal to the base station at a later time. In some of these embodiments data is extracted from the error messages and are stored in a database for future manipulation and retrieval. In some cases the database is resident at a network management station and/or the database is replicated and resident at all or a subset of network base stations and/or a subset of mobile network devices. Also, in some cases, a database of error reports is formed and a set of features is extracted from the database. The features may include determining the actual level of service obtained for the mobile network or to one or more network users. This determines whether the service is satisfactory or unsatisfactory at particular locations and/or to particular users. A feature also enables the database to form a map of dead zones in particular network service areas and/or to examine the database to determine an occurrence of a repetitive time dependent feature.

Still another aspect of the invention is to provide a method for notifying a family of users of the non-operating area of a wireless network. The method

includes steps of obtaining a provided database of the non-operating area of the wireless network, a mobile unit user entering a desired trip route to a vehicle's GPS system, and the vehicle querying the database to download
5 the map for dead zones in the trip route. In some cases the method further includes recommending a changed route having a reduced area of dead zones, and/or the changed route is shown by a GPS screen in the vehicle, and/or providing a warning signal to the user indicating that
10 the vehicle is approaching a dead zone. Sometimes the warning signal includes an audible and/or a visual signal and/or any sensation perception.

In some cases, the user makes a data base query of network reception dead zones, and the network management
15 station responds and determines if the user is entering a dead zone and/or the network management station informs the user of an appropriate step to take to maintain connectivity.

Still a further embodiment of the invention is to provide
20 an error monitoring and collection system for a mobile network. The system includes a plurality of base stations and a plurality of mobile devices wirelessly

interconnected with the base stations. Each device is a member of the mobile network. Each of a subset of the devices includes an error rate monitor to monitor a reception error rate, a message processor to enter into
5 an error reporting mode when the reception error rate rises above a preset threshold. The processor is capable of forming and reporting an error message to a base station.

In some cases the error message is acknowledged by a base
10 station often upon acknowledgment the mobile unit leaves an error reporting mode. Generally, the error message is used by a base station to determine which particular user reported the error and the location of the particular user when the error occurred.

15 Some system embodiments include a network manager which has a database that contains records of all error messages and/or the network manager includes a network processor to extract recurring error trends. In particular embodiment the network processor maps areas of
20 network reception dead zones, and responds to a user request to query the data base to determine if the user is entering a dead zone. Sometimes, the network

processor is able to inform the user of an appropriate step to take to maintain connectivity.

Another aspect of the invention is to provide a program storage device readable by machine, tangibly embodying a
5 program of instructions executable by the machine to perform method steps for notifying a family of users of the non-operating area of a wireless network. The method steps include: providing a database of the non-operating area of the wireless network; a mobile unit user entering
10 at trip route to a vehicle's GPS system; and the vehicle querying the database to download the map for dead zones in the trip route. In some embodiments the method includes recommending a changed route having a reduced area of dead zones and/or the changed route is shown on a
15 GPS screen in the vehicle and/or providing a warning signal to the user indicating that the vehicle is approaching a dead zone.

It is noted that although the description is made for particular arrangements and applications, the intent and
20 concept of the invention is suitable and applicable to other arrangements and applications. It will be clear to those skilled in the art that other modifications to the

Docket Number: YO998167

disclosed embodiments can be effected without departing
from the spirit and scope of the invention.